



FRICTION

Tilt angle 44° (NF Q03-083, 1993 *)

The Grip'N Slip Sheet Push Pull Sheet is made of multiple layers of Kraft Liner board with the top side being laminated with Grip Sheet, a 100% recycled lightweight paper with a non slip coating. Sheets can be made to various sizes and forms to accommodate the customer needs.

TECHNICAL CHARACTERISTICS

TEST	UNITS	STANDARD	NOTE *	RESULT
Paper weight	g/m ²	ISO 536		966
thickness	µm	ISO 534		1457
Bursting strength	kPa	ISO 2758		3060
Tensile strength	kN/m	ISO 1924-2	MD	64,0
			CD	40,5

- * Measurement has been hold in conditions of the norm NF Q03-083, non slide side versus recycled paperboard. The friction coefficient is given as an indication. Friction properties are dependent of the surface, the weight of the product and its dimensions. Before validating the product, a test in real conditions of use is required.
- MD : machine direction :CD : cross direction
- Quantity tolerance per pallet : ±2%
- Tolerance in length and width of sheet : ±2%

REGULATORY

- Compliant to directive 94/62/CE.
- Compliant to REACH regulation
- Usable in food process, indirect contact

HEALTH

- No toxicity
- No skin irritation

ENVIRONMENT

- Issued of recycling fibers
- Entirely recyclable reusable

